



Diclobutrazol Separation on Primesep and Obelisc HPLC Columns

Size: 2.1 x 150 mm
 Flow: 0.4 mL/min
 Detection: UV 270 nm



SIELC has developed the Obelisc™ columns, which are mixed-mode and utilize Liquid Separation Cell technology (LiSC™). These cost-effective columns are the first of their kind to be commercially available and can replace multiple HPLC columns, including reversed-phase (RP), AQ-type reversed-phase, polar-embedded group RP columns, normal-phase, cation-exchange, anion-exchange, ion-exclusion, and HILIC (Hydrophilic Interaction Liquid Chromatography) columns. By controlling just three orthogonal method parameters - buffer concentration, buffer pH, and organic modifier concentration - users can adjust the column properties with pinpoint precision to separate complex mixtures.

Method Parameters

Column	Primesep 100, 2.1x150 mm, 5 µm, 100 Å
Mobile Phase	Gradient MeCN – 10-70%, 15 min
Buffer	Gradient AmAc pH 3.0- 20-60 mM, 15 min
Flow Rate	0.4 mL/min
Detection	UV, 270 nm

Quelle: <https://sielc.com/Application-Diclobutrazol-Separation-on-Primesep-and-Obelisc-HPLC-Columns>